



## **EZ7864 Total Phosphorus/Orthophosphate Analyser, 0.05-10 mg/L TP/PO<sub>4</sub>-P**

**Nr. produs:** EZ7864.XXXXXXXXXX

RON Preț (fără TVA): Contact

Nu este afișată data expirării

### **The full picture of Phosphorus removal: Total Phosphorus and Orthophosphate**

You spend a lot of time looking at your data and your process, so you never come close to any compliance issues while managing your environmental and regulatory goals. When you choose the new EZ Series Total Phosphorus and Orthophosphate analyser from Hach, you'll get industry-leading technology with the power to measure both parameters in one analyser for a full picture of your Phosphorus removal process. Full process insight gives you the confidence to take action.

There are many additional instrument options available. Please contact Hach for more details.

#### **Stay in control**

Monitor your Phosphorus removal process with the reliable data and insights you need to act quickly and with confidence. Phosphorus discharge permits evolve, and the EZ Series Total Phosphorus and Orthophosphate analyser helps you quickly and accurately get both measurements to ensure permit compliance.

#### **See the total picture**

Be confident in your process. You employ biological treatment and/or chemical precipitation to remove Phosphate, but the ratio of effluent TP vs. ortho-PO<sub>4</sub> may vary throughout the day. The new TP/PO<sub>4</sub> analyser will get you actionable data for both parameters with one device. Continuous monitoring will enable you to detect trends. You'll always see both forms of Phosphorus in your water.

#### **This isn't simple, but we'll help you simplify**

Sampling for lab analysis can be time-consuming, costly, and incurs a delay, whereas continuous monitoring helps you to understand the process conditions much faster. The new combined analyser will make your day easier with features that help you save hands-on time. Cooling water is no longer needed. You'll enjoy the autocalibration, self-cleaning and automatic validation this analyser provides. Ready to use reagents and the unparalleled Hach service and support are there to help you optimise your work.

### **Specificații**

|                     |   |
|---------------------|---|
| Alarma:             | 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts   |
| Calibrare:          | Automatic, 2-point; frequency freely programmable   |
| Calitate proba:     | Maximum particle size 100 μm, < 0.1 g/L; Turbidity < 50 NTU   |
| Certificări:        | CE compliant / ETL certified  |
| Clasa de protecție: | Analyser cabinet: IP44 / Panel PC: IP65   |
| Conținutul cutiei:  | EZ7864 Total Phosphorus/Orthophosphate Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and empty Containers for Reagents with Fittings |
| Cuve:               | Standard measurement cycle time for TP & Orthophosphate: 30 minutes   |
| Debitul probei:     | 100 - 300 mL/min  |

|  |  |
|--|--|
| Demineralised water:                       | For rinsing / dilution   |
| Digital outputs:                           | Optional: Modbus (TCP/IP, RS485)   |
| Dimensiuni (Înălțime x Lățime x Adâncime): | 690 mm x 465 mm x 330 mm   |
| Domeniu de măsurare:                       | 0.05 - 10 mg/L TP/PO <sub>4</sub> -P   |
| Earth connection:                          | Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup>  |
| Esantion: presiune:                        | By external overflow vessel  |
| Garanție:                                  | 24 luni  |
| Greutate:                                  | 25 kg  |
| Iesiri analogice:                          | Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)  |
| Instrument air:                            | Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air   |
| Interferente:                              | Arsenic (V), Chromium (VI), Copper (II) > 10 mg/L, Iron (III) > 10 mg/L, Sulphide > 2 mg/L, and Vanadium (V), Silica > 60 mg/L. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar. |
| Limita de detecție:                        | ≤ 0.05 mg/L  |
| Material:                                  | Hinged part: Thermoform ABS, door: PMMA  |
|  | Wall section: Galvanised steel, powder coated  |
| Metoda de măsurare:                        | Colorimetric measurement at 700 nm using ascorbic acid reduction and molybdate colour solution after persulphate digestion in acidic medium, conform with APHA 4500-P  |
| Nr. flux probe :                           | 1, 2, 4, or 8  |
| Parametru:                                 | Total Phosphorus (TP), Orthophosphate (PO <sub>4</sub> -P)   |
| Precizie:                                  | Better than 2% full scale range for standard test solutions  |
| Putere:                                    | 230 VAC, 50/60 Hz  |
|  | 120 VAC, 50/60 Hz  |
|  | Max. power consumption: 440 VA   |
| Reagent Requirements:                      | Keep between 10 - 30 °C  |
| Scurgere:                                  | Atmospheric pressure, vented, min. Ø 32 mm   |
| Temperatura ambiantă:                      | 10 - 30 °C, ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)   |
| Temperatura probă:                         | 10 - 30 °C   |
| Validation:                                | Automatic; frequency freely programmable   |

---

## Conținutul cutiei

EZ7864 Total Phosphorus/Orthophosphate Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and empty Containers for Reagents with Fittings