



EZ3003 Chloride Analyser

Nr. produs:	EZ3003.XXXXXXXXXX
RON Preț (fără TVA):	Contact

Online ion-selective Chloride measurements in industrial and environmental applications

ISE technology for optimal analytical performance

With limited maintenance requirements and reduced reagent consumption, the EZ3000 Series are the ideal choice for a wide range of water monitoring applications where ion-selective electrodes are the preferred analytical technique. Outstanding precision and stability is guaranteed by the temperature-controlled measurement.

Direct, discontinuous ISE method

Contrary to separate electrodes or other analysers in the market, the EZ3000 Series does not run a continuous measurement. The principle of discontinuous ISE analysis not only enhances control over conversion of ion activity to electric potential, it also eliminates risk of cross-contamination between cycles and reduces overall consumption of reagents.

The EZ3000 Series combine unique ISE technology with a set of analysis, control and communication features in an industrial analyser mainframe with designed for the highest performance:

- Automatic direct ion-selective measurements
- Smart automatic features
- Control and communication via industrial panel PC
- Standard 4 - 20 mA signal output with alarm processing
- Communication ports supporting connectivity to Modbus
- Multiple stream analysis
- Reduced reagent consumption

There are many additional options available. Please contact Hach for more details.

Specificații

Alarma:	1x malfunctioning, 4x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Alimentare electrică:	100 - 240 VAC, 50/60 Hz
Calibrare:	Automatic, 2-point; frequency freely programmable

Calitate proba:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Certificări:	CE compliant / UL certified
Clasa de protecție:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65
Conținutul cutiei:	EZ3003 Chloride Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Chloride Electrode and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)
Curatare automata:	Da
Cuve:	5 minutes
Debitul probei:	100 - 300 mL/min
Demineralised water:	For rinsing
Digital outputs:	Optional: Modbus (TCP/IP, RS485)
Dimensiuni (Înălțime x Lățime x Adâncime):	690 mm x 465 mm x 330 mm
Domeniu de măsurare:	1 – 10 mg/L
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²
Esantion: presiune:	By external overflow vessel
Garanție:	24 luni
Greutate:	25 kg
Iesiri analogice:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferente:	Bromide, sulphide, iodide, cyanide ions may interfere. Mercury must be absent. Ammonia and thiosulphate may interfere. Fats, oil, proteins, surfactants and tar.
Limita de detecție:	1 mg/L
Material:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Metoda de măsurare:	Discontinuous, direct measurement by combined ion-selective electrode, conform with standard methods EPA 9212 and ASTM D512-12
Model:	EZ3003
Nr. flux probe :	1, 2, 4 or 8
Nume metoda:	Ionselective
Parametru:	Chloride
Precizie:	Better than 2% full scale range for standard test solutions
Putere:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Reagent Requirements:	Keep between 10 - 30 °C
Scurgere:	Atmospheric pressure, vented, min. Ø 32 mm
Temperatura ambiantă:	10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)
Temperatura probă:	10 - 30 °C
Validation:	Automatic; frequency freely programmable

Conținutul cutiei

EZ3003 Chloride Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Chloride Electrode and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)