



EZ1010 Copper Cu(II) Analyser

Nr. produs: EZ1010.XXXXXXXX

RON Preţ (fără TVA): Contact

Online colorimetric analysis of dissolved Copper in water

EZ1000 Copper Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator invervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Copper Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Specificații

Alarma: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Alimentare electrică: 100 - 240 VAC, 50/60 Hz

Calibrare: Automatic, 2-point; frequency freely programmable

Calitate proba: Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU

Certificări: CE compliant / ETL certified

Clasa de protectie: Protection class: Analyser cabinet: IP44 / Panel PC: IP65

Conținutul cutiei: EZ1010 Copper Analyser, Instruction Manual, 1 x Double Bit Door key, 1 x Mounting Brackets

and 2 x empty 5L Reagent Containers with Fittings (for Colour & Acid Solution)

Curatare automata: Da

Cuve: 10 min (dilution + 5 min)

Debitul probei: 100 - 300 mL/min

Demineralised water: For rinsing / dilution

Digital outputs: Optional: Modbus (TCP/IP, RS485)

Dimensiuni (Înălțime x Lățime x

Adâncime):

690 mm x 465 mm x 330 mm

Domeniu de măsurare: 0.03 - 3 mg/L Cu(II)

Optional:

0.003 - 0.3 mg/L

0.02 - 0.75 mg/L

0.02 - 1.5 mg/L

0.2 - 12 mg/L (with internal dilution)

0.5 - 24 mg/L (with internal dilution)

3 - 300 mg/L (with internal dilution)

Earth connection: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²

Esantion: presiune: By external overflow vessel

Garanție: 24 luni
Greutate: 25 kg

Iesiri analogice: Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Instrument air: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Interferente: Acidity, metal ions like Aluminium (III) > 10 mg/L, Cyanide, Hardness, Iron (III) > 10 mg/L,

Nickel (II) and Silver (II). Large amounts of colour and turbidity interfere. Fats, oil, proteins,

surfactants and tar.

Limita de detecție: $\leq 3 \mu g/L$

Material: Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Metoda de măsurare: Colorimetric measurement at 546 nm using bicinchoninate method; conform respectively with

USEPA Method 8506 and standard method APHA 3500-Cu (C)

Model: EZ1010

Nr. flux probe : 1, 2, 4, or 8

Parametru: Copper, dissolved

Precizie: Better than 2% full scale range for standard test solutions

Putere: 100 - 240 VAC, 50/60 Hz

Max. power consumption: 120 VA

Reagent Requirements: Keep between 10 - 30 °C

Scurgere: Atmospheric pressure, vented, min. Ø 32 mm

Temparatura ambiantă: $10 - 30 \, ^{\circ}\text{C} \pm 4 \, ^{\circ}\text{C}$ deviation at 5 - 95% relative humidity (non-condensing)

Temperatura probă: 10 - 30 °C

Validation: Automatic; frequency freely programmable

Conținutul cutiei
EZ1010 Copper Analyser, Instruction Manual, 1 x Double Bit Door key, 1 x Mounting Brackets and 2 x empty 5L Reagent Containers with Fittings (for Colour & Acid Solution)
Product details pdf footer