



EZ2500 Total Cyanide Analyser

Nr. produs: EZ2500.XXXXXXXXXX
RON Preț (fără TVA): Contact

Online colorimetric analysis of Total Cyanide in water

EZ2000 Total Cyanide Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low $\mu\text{g/L}$ range.

EZ2000 Total Cyanide Analysers have an internal digestion unit. This additional step prior to analysis allows to measure non-soluble or complexed metal species.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Total Cyanide Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be extended via an internal dilution option.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Specificații

Alarma:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Calibrare:	Automatic, 2-point; frequency freely programmable
Certificări:	CE compliant / UL certified
Clasa de protecție:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65

Conținutul cutiei:	EZ2500 Cyanide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 4 x empty 2.5L Reagent Containers with Fittings (for Acid, NaOH, Chlor-T & Buffer Solution) and 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour Solution)
Cuve:	75 minutes (dilution + 5 min.)
Debitul probei:	100 - 300 mL/min
Demineralised water:	For rinsing / dilution
Digital outputs:	Optional: Modbus (TCP/IP, RS485)
Dimensiuni (Înălțime x Lățime x Adâncime):	690 mm x 465 mm x 330 mm
Domeniu de măsurare:	1 - 100 µg/L CN
	Optional:
	100 - 1000 µg/L (with internal dilution)
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm²
Esantion: presiune:	By external overflow vessel
Garanție:	24 luni
Greutate:	25 kg
Iesiri analogice:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferente:	Ions like nitrite > 5 mg/L, sulphide > 100 mg/L and sulphite. Thiocyanate will cause high results. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Limita de detecție:	≤ 1 µg/L
Material:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Metoda de măsurare:	Colorimetric measurement at 578 nm using chloramine T method, conform with standard method APHA 4500-CN €
Nr. flux probe :	1, 2, 4 or 8
Parametru:	Cyanide, total
Precizie:	Better than 5% full scale range for standard test solutions
Putere:	230 VAC, 50/60 Hz
	120 VAC, 50/60 Hz
	Max. power consumption: 440 VA
Reagent Requirements:	Keep between 10 - 30 °C
Scurgere:	Atmospheric pressure, vented, min. Ø 32 mm
Temperatura ambiantă:	10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)
Temperatura probă:	10 - 30 °C
Validation:	Automatic; frequency freely programmable

Conținutul cutiei

EZ2500 Cyanide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 4 x empty 2.5L Reagent Containers with Fittings (for Acid, NaOH, Chlor-T & Buffer Solution) and 1 x empty 2.5L Glass Reagent Container with Fittings (for Colour Solution)