



EZ1030 Phenol Analyser

Nr. produs: **EZ1030.XXXXXXXXXX**
RON Preț (fără TVA): Contact

Online colorimetric analysis of Phenol in water

EZ1000 Phenol Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low $\mu\text{g/L}$ range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Phenol Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Specificații

Alarma:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Alimentare electrică:	100 - 240 VAC, 50/60 Hz
Calibrare:	Automatic, 2-point; frequency freely programmable
Calitate proba:	Maximum particle size 100 μm , < 0.1 g/L; Turbidity < 50 NTU
Certificări:	CE compliant / ETL certified
Clasa de protecție:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65

Conținutul cutiei:	EZ1030 Phenol Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution) and 1 x empty 2.5L Reagent Container with Fittings (for Colour Solution)
Curatare automata:	Da
Cuve:	10 min (dilution + 5 min)
Debitul probei:	100 - 300 mL/min
Demineralised water:	For rinsing / dilution
Digital outputs:	Optional: Modbus (TCP/IP, RS485)
Dimensiuni (Înălțime x Lățime x Adâncime):	690 mm x 465 mm x 330 mm
Domeniu de măsurare:	0.1 - 2 mg/L Phenol
	Optional:
	0.01 - 0.25 mg/L
	0.025 - 0.5 mg/L
	0.025 - 1 mg/L
	0.8 - 8 mg/L (with internal dilution)
	1.6 - 16 mg/L (with internal dilution)
	2 - 200 mg/L (with internal dilution)
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ²
Esantion: presiune:	By external overflow vessel
Garanție:	24 luni
Greutate:	25 kg
Iesiri analogice:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferente:	Oxidising agents such as Chlorine, Sulphur compounds like Sulphide. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Limita de detecție:	≤ 10 µg/L
Material:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Metoda de măsurare:	Colorimetric measurement at 505 nm using 4-aminoantipyrine, conform with standard method APHA
Model:	EZ1030
Nr. flux probe :	1, 2, 4, or 8
Parametru:	Phenol
Precizie:	Better than 3% full scale range for standard test solutions
Putere:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Reagent Requirements:	Keep between 10 - 30 °C
Scurgere:	Atmospheric pressure, vented, min. Ø 32 mm
Temparatura ambiantă:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Temperatura probă:	10 - 30 °C

Conținutul cutiei

EZ1030 Phenol Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution) and 1 x empty 2.5L Reagent Container with Fittings (for Colour Solution)