



Be Right™



EZ2709sc Total Chromium Colorimetric Analyser, 1 stream, 4x mA Output

Nr. produs: EZ2709.980A140T

RON Preț (fără TVA): Contact

Nu este afișată data expedierii

Reliable, Scalable Systems Designed for Peak Performance

The EZ2709sc Total Chromium Analyser, with the advanced SC4500 Controller, provides precise and reliable chromium measurements for improving industrial and wastewater treatment processes. Designed to tackle inefficiencies, ensure regulatory compliance, and fit into existing workflows, the EZ2709sc simplifies process monitoring with dependable results.

Key Features

Flexible Customisation

Adapt the EZ2709sc Total Chromium Analyser to meet your operational requirements. Its standard configuration includes 1 stream and 4x mA outputs, but it can be modified to handle up to 8 streams and 8x mA outputs, offering scalability for more complex applications. With connectivity options such as Modbus RTU, Modbus TCP/IP, Profibus DP, and Ethernet/IP, this Analyser supports seamless integration into diverse system infrastructures for smooth, efficient monitoring.

Reliable and Easy to Use

Designed to perform in demanding environments, the EZ2709sc Total Chromium Analyser ensures consistent, high-accuracy chromium analysis with minimal maintenance. Its intuitive interface and user-friendly approach make setup and operation straightforward, reducing potential errors. Built for long-term durability, this Analyser enables continuous operation, minimising downtime and enhancing overall efficiency.

Explore Tailored Solutions

Each facility has unique needs, and the EZ2709sc Total Chromium Analyser is built with that flexibility in mind. Contact us today to discover how this customisable solution can help optimise your processes, improve efficiency, and ensure confident compliance with your specific requirements.

Trusted Equipment for Critical Operations

The EZ sc Series combines robust engineering with high-quality materials to ensure reliability 24/7. Designed for long-term performance, EZ sc Series minimises breakdowns and supports sustained operational success.

Scalable Solutions for Growing Needs

Built to evolve alongside your needs, online analysers from the EZ sc Series offer adaptable parameters and easier integration. They ensure your facility remains future proof without requiring expensive upgrades. Easily adjust parameter testing ranges and expand sample streams to accommodate innovation and growth.

Real-Time Data for Faster Decisions

The EZ sc Series offers advanced connectivity and real-time monitoring, delivering immediate access to actionable insights. Facilities utilising this technology benefit from improved reaction times, empowering more informed decision-making and quicker responses during critical situations.

Simplified Troubleshooting with Expert Support

Built-in diagnostics combined with secure remote data access make the EZ sc Series simplify issue resolution. Supported by a highly responsive team of experts, it ensures uninterrupted functionality and minimises operational downtime. By addressing and identifying issues early, EZ sc Series of online analysers helps prevent costly disruptions and repairs while maintaining system efficiency.

Clear Workflows for Predictable Outcomes

Standardised tools and guided workflows ensure consistent implementation and operation. The EZ sc Series minimises miscommunication, sets clear expectations, and reduces process inconsistencies, driving greater efficiency.

Specificații

Calibrare:	Automatic; 2-point; offset or slope; Frequency freely programmable: 6 hours, 12 hours, daily, weekly. Note: manufacturer recommends that a calibration is done when the reagents are replaced
Calitate proba:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Carcasă impermeabilă (IP) :	IP44
Certificări:	CE, ETL certified to UL and CSA safety standards, UKCA
Clasa de protecție:	IP44
Conținutul cutiei:	EZ2709sc Total Chromium Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 3 x empty 2.5 L Reagent Containers with Fittings (for Acid, Persulphate & Buffer Solution) and 1 x empty 2.5 L Glass Reagent Container with Fittings (for Colour Solution)
Cooling water:	Flow rate approx. 5 L/h; temperature max. 30 °C; pressure max. 0.5 bar
Curatare automata:	Yes; Frequency freely programmable: 6 hours, 12 hours, daily, weekly
Cuve:	No Dilution Default: 45 min. Continuous: 34 min. Internal Dilution Default: 45 min. Continuous: 38 min.
Debitul probei:	100 - 300 mL/min
Demineralised water:	Internal dilution option: Rinse water & Dilution water
Digital outputs:	Profibus DP or Modbus RTU
Dimensiuni (Înălțime x Lățime x Adâncime):	688 mm x 460 mm x 340 mm
Domeniu de măsurare:	No Dilution 0.005 - 0.5 mg/L Cr(T): 0.005 mg/L Internal Dilution 0.025 - 2.5 mg/L Cr(T): 0.025 mg/L
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ²
Esantion: presiune:	By external overflow vessel (open to atmospheric pressure)
Garanție:	24 luni
Greutate:	Max. 35 kg

Ieşire:	Optional: Claros Ethernet connection and Modbus TCP/IP Ethernet connector; LAN version; 10/100 Mbps or Profinet or Ethernet IP
Iesiri analogice:	Active 0 - 20 mA (or 4 - 20 mA) max. 500 Ohm load, standard 4, optional: 8
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air. Used to flush the instrument in corrosive environment. Min. 0.2 bar - Max. 0.5 bar
Interferente:	Iron (III) [(Fe) ³⁺], mercury [(Hg) ²⁺] > 200 mg/L, molybdenum [(Mo) ²⁺] > 200 mg/L, vanadium (V) [(V) ⁵⁺] > 5 mg/L, Alkalinity (CaCO ₃) > 1000 mg/L, COD (O ₂) > 500 mg/L. Large amounts of color and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Limita de detecție:	No Dilution 0.005 - 0.5 mg/L Cr(T): 0.005 mg/L Internal Dilution 0.025 - 2.5 mg/L Cr(T): 0.025 mg/L
Material:	Hinged part: Thermoform ABS, door: PMMA Wall section: Galvanised steel, powder coated
Metoda de măsurare:	Colorimetric
Metoda de masurare:	Diphenylcarbazide colorimetric method
Model:	EZ2709sc
Nr. flux probe :	Standard: 1 Optional accessory for 2, 4, or 8 sample streams
Parametru:	Chromium, total
Precizie:	Better than 2% full scale range for standard test solutions
Putere:	230 VAC, 50/60 Hz Max. power consumption: 240 VA
Reagent Requirements:	Keep colour solution between 5 - 10 °C, all other reagents between 10 - 30 °C
Relee:	5 contacts, not user configurable: Malfunction, maintenance, analysis ready, sample ready, sample ready (EZ9150)
Scurgere:	Atmospheric pressure, vented, min. Ø 32 mm
Temperatura ambientă:	10 - 30 °C (50 - 86°F) ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Temperatura probă:	10 - 30 °C
Validation:	Automatic; Frequency freely programmable: 6 hours, 12 hours, daily, weekly

Conținutul cutiei

EZ2709sc Total Chromium Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 3 x empty 2.5 L Reagent Containers with Fittings (for Acid, Persulphate & Buffer Solution) and 1 x empty 2.5 L Glass Reagent Container with Fittings (for Colour Solution)